

Technical data sheet Version 2

Acrylic lacquer TY 2316-003-49630959-04

Purpose	For protective and decorative finishing of wood, brick, concrete inside and outside.	
Properties	Provides long-term protection against rot, blue stain, mold, mildew, fungus, wood insects. Forms a wear-resistant coating with water-repellent properties. Can be tinted with tinting compounds and tinting pastes.	
Name	Wd.291, Acrylic semi-matt with UV protection GOLwood Wd.290, Acrylic semi-matt on wood and other surfaces GOLwood Wd.292, Acrylic high gloss lacquer on wood and other surfaces GOLwood	
Composition	Water Styrene acrylic latex Special additives.	
Packing	Plastic containers weighing 0.9 kg, 2.4 kg, 9 kg.	

Technical Specifications

Appearance		Composition in white
Viscosity according to VZ-246 viscometer, nozzle diameter 4 mm, sec, no less		· ·
Mass fraction of non-volatile substances, %, no less		23
Frost resistance, cycles		5
рН		8-9
Drying time up to degree 3		1
at (20±2) oC, hour, not more		24
Total drying time, hour		70-100 г/м ²
Storage conditions	Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5oC. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.	
Guaranteed shelf life	In unopened container date of manufacture.	manufacturer 24 months from the

 Transporting
 By all means of transport in conditions excluding the influence

	of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.
Waste disposal	Containers and unused remains of varnish after drying are disposed as household waste.
Safety	Products are fire and explosion-proof and non-toxic. Use personal hand protection equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to The published technical data and instructions are subject to change without notice.