

Technical data sheet
Version 1

Impregnation
Antiseptic-superbio
TU 2386-007-49630959-04

Destination For enhanced protection of wood, concrete, brick and other surfaces in particularly harsh environments. Prevents and destroys biodegradation.

Properties Tints the wood into a greenish-olive color. Does not have an unpleasant odor. Resistant to washout.

Composition Aqueous solution of salts.

Packaging Plastic containers weighing 1kg, 5kg, 10kg, 30kg.

Technical Specifications

Appearance	Greenish-pistachio liquid, slight turbidity and sediment allowed
Density at 20°C, g/cm ³	1,08-1,12
Frost resistance, cycles	5
Application temperature, °C, not less	+8
pH	2,5-5,5
Time of complete drying, hour	24
Consumption (per coat)	1 liter per 3-5 m ²

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5°C. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

Guaranteed shelf life In unopened container manufacturer 60 months from the date of manufacture.

Transportation By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous

goods. Code of emergency measures is not required.

Waste management

Containers and unused remains of impregnation after drying are disposed of as household waste.

Security

Products are fire and explosion-proof and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil. Do not use on metal, painted, glass surfaces and tiles.

All information is correct on the day of publication. Published technical data and instructions may be changed without prior notice.