



Technical data sheet Version 2

Acrylic glossy enamel

ТУ 2316-010-49630959-14

Purpose For painting primed wooden, brick, concrete, plastered, gypsum plasterboard surfaces, except floors, metal surfaces.

Properties Tintable with pastes of series SS-980, Palineth color, UPC, Palizh Mix. Colored enamels are used without tinting. It is used for exterior and interior works.

Composition Water
Antifreeze
Acrylic dispersion
Special additives
Pigment

Packing Plastic containers with mass for white 1,1 kg, 2,5 kg, 12 kg, 30 kg
Plastic containers with mass for all other colors 1 kg, 2,5 kg, 10 kg, 30 kg

Colors

- White
- Beige
- Dark brown
- Red-brown
- Red
- Yellow
- Green
- Blue
- Black

Technical Specifications

Appearance	Homogeneous liquid of appropriate color
Appearance after drying	Homogeneous, with no craters, pores or wrinkles. Minor shagging is acceptable.
Bruckfield viscosity, cPs, sp. 5, V=20 rpm, 25°C	6000-8000
Mass fraction of non-volatile substances, %, min	45
Grind degree, micron, not more	10
Shine, not less	50-60

Film resistance to static action of water at (20±2)°C, h, no less	72
Density at 20°C, g/cm ³	1,1-1,4
Frost resistance, cycles	5
pH	6,5-8,5
Drying time up to degree 3 at (20±2) oC, hour, not more	1
	24

Storage conditions

Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5oC. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it fully retains its properties.

Guaranteed shelf life

In unopened container manufacturer 24 months from the date of manufacture.

Transporting

By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste disposal

Containers and unused remnants of enamel after drying are disposed of as household waste.

Safety

Products are fire and explosion-proof and non-toxic. Use personal hand protection equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the date of publication. Published technical data and instructions are subject to change without notice.