

Technical data sheet Version 1

Acrylic putty INTERIOR GOExpert

ТУ 2316-006-49630959-04

Purpose For leveling the plastered surfaces of walls and ceilings, for sealing the gaps of baseboards inside the premises.

Properties Dries quickly, is easy to sand, does not drag behind painting tools.

Composition Acrylic latex
Water
Filler
Special Additives

Packing Plastic containers weighing 1.5 kg, 4.5 kg, 15 kg.

Technical Specifications

Appearance	Homogeneous paste of white to creamy color
Mass fraction of non-volatile substances, %, no less	60
Frost resistance, cycles	5
Temperature of application, oC, not less	+8
Drying time up to degree 3 at a temperature of (20±2) oC, hour, not more	3
Total drying time, hour	24

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5oC. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

Guaranteed shelf life In unopened container manufacturer 18 months from the date of manufacture.

Transporting By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not

exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste management

Containers and unused putty residue after drying are disposed of as household waste.

Safety

Products are fire and explosion-proof and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to change without notice.