



Technical data sheet Version 1

Color washable acrylic interior paint

TY 2316-005-49630959-04

Purpose For high-quality decorative finishing of walls and ceilings indoors on plasterboard, brick, concrete, plaster, wood, all types of wallpaper and other surfaces (except floors).

Properties Resistant to repeated wet cleaning. Does not burn out when exposed to sunlight.

Composition Acrylic latex
Micronized marble
Titanium Dioxide
Water
Targeted micro-additives
Pigments

Colors		
	<ul style="list-style-type: none">• Ginger• Tiramisu• Almonds• Crème brûlée• Vanilla• Green tea• Mojito• Peppermint	<ul style="list-style-type: none">• Blue Ice• Juniper• Halva• Saffron• Barberry• Rosemary• Lavender• Plombard• Black truffle

Packing Plastic container with a capacity of 3.7 kg

Technical Specifications

Appearance	Homogeneous mass of a certain color
Film appearance after drying	Smooth, no visible inclusions
Bruckfeld viscosity, cPs, sp. 5, V=20 rpm, 25°C	5000-6000
Grind degree, µm, not more	30
Mass fraction of non-volatile substances, %, min	50
Film resistance to static influence of water at (20±2)°C, h, no less	24
Frost resistance, cycles	5
pH	6,5-9,6

Application temperature, °C, not less	+8
Drying time up to degree 3	1
at (20±2) oC, hour, not more	24

Storage conditions

Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not below 0oC. In case of freezing, thaw products at room temperature and mix thoroughly until homogeneous mass. After thawing it retains its full properties.

Guaranteed shelf life

In unopened container manufacturer 24 months from the date of manufacture.

Transportation

By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste management

Containers and unused paint residue are disposed of as household waste after drying.

Safety

The paint is flame retardant and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to change without notice.