

Technical data sheet Version 2

Acrylic wood filler ТУ 2316-006-49630959-04

Purpose	To correct wood defects.	
Properties	Fast drying, easy to sand, fills irregularities evenly. Does not shrink.	
Composition	Acrylic latex Water Filler Special Additives	
Colors	Pine Light Oak Dark Oak Larch Mahogany Beech	White Light Pine Rosewood Mahogany Dark Walnut Ebony
Packing	Plastic containers weighing 0.15kg, 0.62kg, 0.65kg.	
Technical Specifications		
Appearance of coating	homogeneous paste of a certain color	
Frost resistance, cycles	5	
Temperature of application, oC, not less	+8	
Drying time up to degree 3	3	
at (20±2) oC, hour, not more	24	
Storage conditions	Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5oC. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties	
Guaranteed shelf life	In unopened container manufacturer 18 months from the date of manufacture.	

Transporting

By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste disposal

Containers and unused putty residue after drying are disposed of as household waste.

Safety

Products are fire and explosion-proof and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to change without notice.