

Technical data sheet Version 2

Paint for garden trees

ТУ 2316-005-49630959-04

Purpose For painting trunks of garden trees.

Properties Protects bark from sunburn, insect pests and the negative effects of low temperatures. Does not interfere with breathing.

Composition Water
Micronized marble
Acrylic latex
Targeted additives

Packing Plastic containers weighing 0.9kg, 2.5kg, 6kg, 15kg

Technical Specifications

Appearance	Homogeneous mass of white color
Film appearance after drying	Smooth, no visible inclusions
Bruckfield viscosity, cPs, spindle 5, V=20 rpm, 25°C	2000-5000
Frost resistance, cycles	5
Temperature of application, °C, not lower	+8
Drying time up to degree 3	1
at (20±2) °C, hour, not more	24

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5°C. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

Guaranteed shelf life In unopened container manufacturer 36 months from the date of manufacture.

Transportation By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste disposal

Containers and unused paint residue are disposed of as household waste after drying.

Safety

The paint is flame retardant and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to change without notice.