

## Technical data sheet

## "STANDART" universal coloring paste

TU 2316-001-49630959-02

**PURPOSE** FOR COLORING PAINTS, VARNISHES, ENAMELS, PUTTY PASTES, GROUTS, PLASTER, PLASTER BLENDS, TREATMENT COMPOUNDS, PRIMERS

---

**SPECIAL CONDITIONS** TESTING BEFORE APPLICATION IS RECOMMENDED. SHADE MAY DIFFER DEPENDING ON THE TYPE AND QUALITY OF THE PAINT USED

---

**COMPOSITION** PIGMENT  
POLYATOMIC ALCOHOL  
ADDITIVES

---

**COLOR RANGE**

○ LEMON-YELLOW	○ GREEN	○ SCARLET
○ GOLDEN-YELLOW	● APPLE-GREEN	○ DARK BLUE
○ BRIGHT YELLOW	● KHAKI	● CARAMEL
● YELLOWY-BROWN (ochre)	● PISTACHIO	● CHOCOLATE
● BEIGE	● COFFEE	○ BURGUNDY
● LIGHT BROWN	● DARK BROWN	○ LAVENDER
○ ORANGE	● BLACK	● TURQUOISE
○ PEACH	● GREY-BLUE	● AQUAMARINE
○ CORAL	● ULTRAMARINE	○ BLUEBERRY
○ DARK RED	○ LIME	● FUCHSIA
○ PINK	● IVORY	● GRAPHITE
● PURPLE	● RED-CINNAMONIC	○ SUNNY
○ PLUM	○ TANGERINE	● LIGHT BLUE
○ LILAC	● PALE-YELLOW	● PEARL
● IRIS	● DARK GREEN	● BRONZE
● VIOLET	● GOLD	
● BLUE	● SILVER	
○ LIGHT GREEN		
● SEA-GREEN		

● - For internal and exterior works

○ - For internal works

---

**PACKAGE** PLASTIC CONTAINERS 0,1 L; 0,9 L; 0,45 L

---

## TECHNICAL SPECIFICATIONS

Exterior	Viscous colored opaque mass
Brookfield Viscosity, cps shp.5, V = 100 r/min, 25 °C	350-3000
Grinding, mkm	40
Density at 20 °C, g/cm <sup>3</sup>	1,24-1,58
Freeze thaw resistance, cycles	5
pH	7,5-11

**STORAGE CONDITIONS** Store in tightly closed containers, away from heaters and direct sunlight, at the temperatures from +5 to +50 °C.

**WARRANTY PERIOD OF STORAGE** In unopened manufacturer's container 36 months from the date of manufacture.

**TRANSPORTATION** It is allowed to transport the concentrate in the original container by all the types of transport in conditions that exclude the influence of atmospheric factors (covered vans, wagons, etc.) at a temperature of ±50°C. Duration of transportation at temperatures below 0 °C should not exceed 1 month. The product does not apply to dangerous goods. Exception code is not required.

**RECYCLING** Container and unused residues are disposed as household waste.

**SAFETY** Universal coloring paste is fire and explosion proof, does not burn, is not subject to thermal decomposition. To protect the skin of hands, use gloves made of polymeric materials (rubber, latex, polyethylene). In case of contact with eyes or skin, rinse immediately with water. After the end of work, wash the containers and tools with water.

**CERTIFICATE** REGISTRATION CERTIFICATE RU.18.YLQ.04.008.E000010.02.14 add 04.02.2014

All information is correct on the day of publication. Published technical data and instructions are subject to change without prior notice.