

Technical data sheet Version 2

FASADE acrylic paint

ТУ 2316-005-49630959-04

Purpose	For exterior and interior painting of brick, concrete, plastered, wooden and other surfaces (except floors), including rooms with high humidity (baths, kitchens).
Properties	Forms a matte, uniform, smooth, moisture-resistant, weather-resistant, vapor-permeable coating. Can be tinted with water and universal tinting pastes in pastel colors. Suitable for hand and machine tinting.
Composition	Water Acrylic latex Micronized marble Titanium Dioxide Targeted micro-additives
Packing	Plastic containers weighing 1.4 kg, 3 kg, 6.5 kg, 13 kg, 35 kg

Technical Specifications

Appearance		Homogeneous mass of white color
Film appearance after drying		Smooth, no visible inclusions
Bruckfield viscosity, cPs, spindle #5, V=20 rpm, 25°C		5000-6000
Grind degree, μm, not more		30
Mass fraction of non-volatile substances, %, no less		50
Film resistance to static impact of water at (20+2)°C, h, no less		24
Frost resistance, cycles		5
рН		6,5-9,5
Temperature of application, °C, not less		+8
Drying time up to degree 3		1
at (20±2) oC, hour, not more		24
Total drying time, hour		150г/м²
Storage conditions	direct sunlight, at a ten	container, away from heaters and nperature not lower than +5oC. In the sthaw at room temperature and mix

	thoroughly until homogeneous mass. After thawing it completely retains its properties.
Guaranteed shelf life	In unopened container manufacturer 24 months from the date of manufacture.
Transporting	By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.
Waste management	Containers and unused paint residue are disposed of as household waste after drying.
Safety	The paint is flame retardant and non-toxic. Wear personal protective equipment for hands. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil.

All information is correct on the day of publication. Published technical data and instructions are subject to The published technical data and instructions are subject to change without notice.