

Technical data sheet Version 1

Impregnation Antiseptic-bio

ТУ 20.20.15-007-49630959

Purpose To protect wooden, brick, concrete surfaces against mold, mildew, fungus, woodworms in conditions of moderate moisture inside the home.

Properties Does not tint the wood. Does not have an unpleasant odor.

Composition Aqueous solution of salts.

Packing Plastic containers weighing 1kg, 5kg, 10kg, 30kg.

Technical Specifications

Appearance	Colorless or light straw liquid, slight turbidity and sediment possible
Density at 20°C, g/cm ³	1,03-1,12
Frost resistance, cycles	5
Temperature of application, °C, not less	+8
pH	6-9
Total drying time, hour	24
Consumption (for one coat)	1 л на 3-5 м ²

Storage conditions Store in a tightly closed container, away from heaters and direct sunlight, at a temperature not lower than +5°C. In case of freezing products thaw at room temperature and mix thoroughly until homogeneous mass. After thawing it completely retains its properties.

Guaranteed shelf life In unopened container manufacturer 60 months from the date of manufacture.

Transportation By all means of transport in conditions excluding the influence of atmospheric factors (covered vans, wagons, etc.). Duration of transportation at temperatures below 0°C should not exceed 1 month. Product does not belong to dangerous goods. Code of emergency measures is not required.

Waste management

Containers and unused remains of impregnation after drying are disposed of as household waste.

Safety

Products are fire and explosion-proof and non-toxic. Use personal protective equipment. When using the product do not smoke, do not drink, do not eat. In case of contact with skin and eyes wash with water. Keep out of reach of children. Avoid contact with water and soil. Do not use on metal, painted, glass surfaces and tiles.

All information is correct on the day of publication. Published technical data and instructions are subject to change without notice.